TECHNICAL DATA

iFlood

PRODUCT CODE

FL100-RGB-CCT



WARRANTY

3 years guarantee

@GAPLightingLtd

GAP Lighting Ltd

/GAPLightingLtd

GAP Lighting Ltd

SMART SYNC




PRODUCT DESCRIPTION

New revolutionary high powered LED floodlight with RGB+CCT technology and WiFi control offering the ultimate solution for colourful wallwash. Multi colour options and adjustable white temperature will create different lighting experiences to best suit the environment and occasion. Control independently or synchronise with other SMART SYNC products.







T-4Z-REMOTE

PRODUCT FEATURES

High powered RGBCCT LED Floodlight

CCT tunable white temperature 2700k-6500k

Multi program RGB colour changing

Ultra slim-line design

Smooth dimming control

25 beam angle for intense spotlight effect

Up to 30 metres remote range

IP65 protection

Black die-cast aluminium housing

Use independently or synchronise with other units

Suitable for domestic and commercial application $\label{eq:commercial} % \[\mathcal{L}_{\mathcal{L}} = \mathcal{L}_{\mathcal{$

PRODUCT DATA

ModelFL100-RGB-CCTLED BrandEPISTARPower100WLuminous Flux8000LmProtectionIP65CRI>80ColourTunable 2700k - 6500k + RGB Colour Changing optionsInput240VMaterialBlack die-cast aluminium housing glass lensBeam Angle25°Life>30,000 hoursControl2.4G RF - App control Remote controlWireless SignalRF 2.4GhzRangeUp to 30m (without obstruction)DimensionsH 345mm W 330mm D 60mmApprovalsCE ROHS		
Power 100W Luminous Flux 8000Lm Protection IP65 CRI >80 Colour Tunable 2700k - 6500k + RGB Colour Changing options Input 240V Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Model	FL100-RGB-CCT
Luminous Flux 8000Lm Protection IP65 CRI >80 Colour Tunable 2700k - 6500k + RGB Colour Changing options Input 240V Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	LED Brand	EPISTAR
Protection IP65 CRI >80 Colour Tunable 2700k - 6500k + RGB Colour Changing options Input 240V Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Power	100W
CRI >80 Colour Tunable 2700k - 6500k + RGB Colour Changing options Input 240V Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Luminous Flux	8000Lm
Colour Tunable 2700k - 6500k + RGB Colour Changing options Input 240V Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Protection	IP65
Input 240V Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	CRI	>80
Material Black die-cast aluminium housing glass lens Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Colour	Tunable 2700k - 6500k + RGB Colour Changing options
Beam Angle 25° Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Input	240V
Life >30,000 hours Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Material	Black die-cast aluminium housing glass lens
Control 2.4G RF - App control Remote control Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Beam Angle	25°
Wireless Signal RF 2.4Ghz Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Life	>30,000 hours
Range Up to 30m (without obstruction) Dimensions H 345mm W 330mm D 60mm	Control	2.4G RF - App control Remote control
Dimensions H 345mm W 330mm D 60mm	Wireless Signal	RF 2.4Ghz
	Range	Up to 30m (without obstruction)
Approvals CE ROHS	Dimensions	H 345mm W 330mm D 60mm
	Approvals	CE ROHS

CONTROL OPTIONS

T-WIFI2 - smart phone control T-8Z-REMOTE T-RGB-CCT T-4Z-REMOTE WIRING

240V Direct to mains