+44 1322 620 100

www.gaplighting.co.uk

WARRANTY

@GAPLightingLtd

GAP Lighting Ltd

/GAPLightingLtd

GAP Lighting Ltd

1 year guarantee

9

in

f f

TECHNICAL DATA

CONTROL & POWER

PRODUCT CODE

T-100W-12VDC



PRODUCT DESCRIPTION

All 12v products require a constant voltage power supply and should be wired in parallel. IP rated pre-wired power supplies are also available for 100-350w.

COMPATIBILITY CHART

CODE	MAX LOAD
SL-LED4.8	18M
SL-LED7.2	12M
SL-IP654.8	18M
SL-IP657.2	12M
SL-IP684.8	18M
SL-IP687.2	12M
GL102-RGB	1-100
GL108	1-100
GL0140-RGBW/WW	1-25
ML103-RGB	1-50

PRODUCT DATA

PRODUCT FEATURES

12v constant voltage LED driver

Covered screw terminals

For use with 12vDC LED luminaires

For indoor use or within an enclosure

Metal housing

Dual terminals on output

Voltage adjust screw

Mounting tabs for securing to a flat surface

Wire direct to LED or to a T-CON5 for 12v colour changing LED

Do not exceed 90% load of the driver

Suitable for interior architectural, retail and commercial applications.



12v LED Strip

Will power up to 12m of 7.2w/m or 18m of 4.8w/m FLEX20 / FLEX65 / AQUAFLEX

INSTALLATION

Please follow installation guide

Model	T-100W-12VDC
Power	100w
Output Voltage	12v constant voltage
Output Current	8.5A max
Input	100-120vAC 2.4A 200 - 240vAC 1.2A 50/60Hz
Working Temp.	=0° C - 60°C
Protection	IP20
Dimensions	L 198mm W 98mm D 38mm
Weight	530g
Approvals	CE ROHS

