info@gaplighting.co.uk

TECHNICAL DATA

CONTROL & POWER

PRODUCT CODE

T-12W-350MA



WARRANTY

1 year guarantee

@GAPLightingLtd

GAP Lighting Ltd

/GAPLightingLtd

GAP Lighting Ltd





PRODUCT DESCRIPTION

Constant current 350mA driver for use with series wired GAP LED fittings. Wire in series. Non-dimmable.

PRODUCT FEATURES

12w constant current non-dimmable LED driver

Covered terminal connections

For use with constant current LED luminaires

For indoor use or within an enclosure

PC housing

Mounting tabs for securing to a flat surface

Protections: Short Circuit / Over Load / Over Current

Cooling by free air convection

Suitable for interior architectural, retail and commercial applications.

COMPATIBILITY CHART

GLM12

CODE	MAX LOAD	CODE
LED03 GL102/H/SQ GL106/H/Q GL109/Q/QT GL0140 GL121/122/123 GL0151/2/4 PL1021 PL1023 PL1026	1-4 2-10 2-10 2-10 1-3 2-10 1-3 2-10 1-3	ML103 ML304 ML0021 ML0022
FLIUZU	I	

Χ

PRODUCT DATA

Model	T-12W-350MA	
Rated Current	350mA +/- 35mA	
DC Voltage	Max 34v	
Rated Power	12w	
AC Current	<0.2A	
Working Temp.	-20° to +45°C Ta: Max 45°C Tc: Max 80°C	
Protection	IP20	
Dimensions	L 125mm W 48mm D 10mm	
Current Tolerance	+/- 10%	
Voltage Range	200-240VAC +/-10% 50-60Hz	
Primary cable	H03VVH2-F 2x0.75mm ₂	
Secondary cable	H03VVH2-F 2x0.75mm ₂	
Weight	60g	
Approvals	CE RoHS SELV	

MAX LOAD

2-10	
1-3	
2-10	
1-5	

INSTALLATION

Please follow installation guide