## TECHNICAL DATA
## CONTROL & POWER

### PRODUCT CODE

T-30W-12VDC

**GAP lighting**
Smart LED Solutions

### WARRANTY

1 year guarantee

@GAPLightingLtd

GAP Lighting Ltd

/GAPLightingLtd

GAP Lighting Ltd

### PRODUCT DESCRIPTION

All 12v products require a constant voltage power supply and should be wired in parallel.
IP rated pre-wired power supplies are also available for 100-350w.

### COMPATIBILITY CHART

| CODE | MAX LOAD |
|---|---|
| SL-LED4.8 | 5M |
| SL-LED7.2 | 3M |
| SL-IP654.8 | 5M |
| SL-IP657.2 | 3M |
| SL-IP684.8 | 5M |
| SL-IP687.2 | 3M |
| GL102-RGB | 1-44 |
| GL108 | 1-50 |
| GL0140-RGBW/WW | 1-7 |
| ML103-RGB | 1-20 |

### PRODUCT FEATURES

12v constant voltage LED driver

Pre-wired connections

For use with 12vDC LED luminaires

For indoor use or within an enclosure

PC housing

Mounting tabs for securing to a flat surface

Wire direct to LED or to a T-CON5 for 12v colour changing LED

Do not exceed 90% load of the driver

Suitable for interior architectural, retail and commercial applications.

### PRODUCT DATA

| Model | T-30W-12VDC |
|---|---|
| Power | 30w |
| Output Voltage | 12v constant voltage, 2500mA (MAX) |
| Output Current | 900mA max. |
| Input | 220 - 240v  50/60Hz |
| Working Temp. | -5° to +60° |
| Temperatures | Ta: 45°C     Tc: 85°C |
| Protection | IP20 |
| Dimensions | L 153mm | W 49mm | D 28mm |
| Weight | 0.2kg |
| Approvals | CE | ROHS |

**12v LED Strip**

Will power up to 3m of 7.2w/m or 5m of 4.8w/m
FLEX20 / FLEX65 / AQUAFLEX

### INSTALLATION

Please follow installation guide

Unit 14-15 Schooner Court | Crossways Business Park | Kent | DA2 6NW
Tel. +44 (0) 1322 620 100 | Email. info@gaplighting.co.uk
www.gaplighting.co.uk