

TECHNICAL DATA  
CONTROL & POWER

WARRANTY  
1 year guarantee

PRODUCT CODE

T-4W-350MA



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

Constant current 350mA driver for use with series wired GAP LED fittings.  
Wire in series.  
Non-dimmable.

PRODUCT FEATURES

- 4w constant current non-dimmable LED driver
- Pre-wired connections
- For use with constant current LED luminaires
- For indoor use or within an enclosure
- PC housing
- Mounting tabs for securing to a flat surface
- Protections: Short Circuit / Over Load / Over Current
- Cooling by free air convection
- Suitable for interior architectural, retail and commercial applications.

PRODUCT DATA

Model	T-4W-350MA
Rated Current	350mA +/-10%
DC Voltage	3-12vDC
Rated Power	4w
AC Current	0.15A
Working Temp.	-20° to +50°C Ta: Max 50°C Tc: Max 85°C
Protection	IP66
Dimensions	L 53mm   W 27mm   D 20mm
Current Tolerance	+/- 10%
Voltage Range	100-240VAC +/-10% 50-60Hz
Primary cable	UL1007 18AWG 180mm
Secondary cable	UL1007 18AWG 180mm
Weight	42g
Approvals	CE   RoHS   SELV

COMPATIBILITY CHART

CODE	MAX LOAD	CODE	MAX LOAD
LED03	1	ML103	1-3
GL102/H/SQ	1-3	ML304	1
GL106/H/Q	1-3	ML0021	1-3
GL109/Q/QT	1-3	ML0022	1
GL0140	1		
GL121/122/123	1-3		
GL0151/2/4	1		
PL1021	1-3		
PL1023	1		
PL1026	X		
GLM12	X		

INSTALLATION

Please follow installation guide