info@gaplighting.co.uk

## TECHNICAL DATA

## **CONTROL & POWER**

# PRODUCT CODE

T-60W-12VDC





1 year guarantee

@GAPLightingLtd

GAP Lighting Ltd in

/GAPLightingLtd **f** 





## PRODUCT DESCRIPTION

All 12v products require a constant voltage power supply and should be wired in parallel. IP rated pre-wired power supplies are also available for 100-350w.

## **COMPATIBILITY CHART**

CODE	MAX LOAD
SL-LED4.8	11M
SL-LED7.2	7M
SL-IP654.8	11M
SL-IP657.2	7M
SL-IP684.8	11M
SL-IP687.2	7M
GL102-RGB	1-100
GL108	1-100
GL0140-RGBW/WW	1-15
ML103-RGB	1-30

## PRODUCT FEATURES

12v constant voltage LED driver

Pre-wired connections

For use with 12vDC LED luminaires

For indoor use or within an enclosure

PC housing

Dual terminals on input and output

Mounting tabs for securing to a flat surface

Wire direct to LED or to a T-CON5 for 12v colour changing LED

Do not exceed 90% load of the driver

Suitable for interior architectural, retail and commercial applications.

## PRODUCT DATA

Model	T-60W-12VDC
Power	60w
Output Voltage	12v constant voltage,
Output Current	5000 mA max
Input	220 - 240v 50/60Hz
Temperature	Ta: 45° C Tc: 85° C
Protection	IP20
Dimensions	L 175mm   W 50mm   D 38mm
Weight	0.2kg
Approvals	CE   ROHS



12v LED Strip

Will power up to 7m of 7.2w/m or 11m of 4.8w/m FLEX20/FLEX65/AQUAFLEX

INSTALLATION

Please follow installation guide