

TECHNICAL DATA  
CONTROL & POWER

WARRANTY  
1 year guarantee

PRODUCT CODE

TDIM-15W-350



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

Constant current Triac dimmable driver with multiple levels selectable by dip switch. Select 350mA current level to use with GAP 350mA LED fittings. Wire in series. Compatible with Triac and Phase cut dimmers.

PRODUCT FEATURES

- 15w constant current Triac dimmable LED driver
- Screw terminal connections
- For use with constant current LED luminaires
- For indoor use or within an enclosure
- PC housing
- Mounting tabs for securing to a flat surface
- Protections: Short Circuit / Over Load / Over Current
- Cooling by free air convection
- Dimming function: Triac dimmable; Phase Cut dimmable
- Suitable for interior architectural, retail and commercial applications.

PRODUCT DATA

Model	TDIM-15W-350							
Rated Current	700mA	600mA	500mA	450mA	400mA	350mA	250mA	150mA
DC Voltage	3-22v	3-25v	3-30v	3-33v	3-37v	3-45v	3-50v	20-50v
Rated Power	15.4w	15w	15w	14.85w	14.8w	15.75w	12.5w	7.5w
AC Current	0.17A	0.16A	0.16A	0.16A	0.16A	0.17A	0.14A	0.08A
Working Temp.	-40° to +80°C, 1095%RH							
Protection	IP20							
Dimensions	L 140mm   W 45mm   D 27mm							
Current Tolerance	+/- 5%							
Voltage Range	180-240VAC 47-63Hz							
Inrush Current	15A (Twidth=270µs 230VAC)							
Over Load	≤120%							
Weight	19g							
Approvals	CE   SELV   EN61347-1   EN61347-2-13							

COMPATIBILITY CHART

CODE	MAX LOAD	CODE	MAX LOAD
LED03	1-4	ML103	2-14
GL102/H/SQ	2-14	ML304	1-4
GL106/H/Q	2-14	ML0021	2-14
GL109/Q/QT	2-14	ML0022	1-7
GL0140	1-4		
GL121/122/123	2-14		
GL0151/2/4	1-4		
PL1021	2-14		
PL1023	1-4		
PL1026	1-2		
GLM12	1		

INSTALLATION

Please follow installation guide