

TECHNICAL DATA  
CONTROL & POWER

WARRANTY  
1 year guarantee

PRODUCT CODE

TDIM-25W-350



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

Constant current Triac dimmable driver with multiple levels selectable by dip switch. Select 350mA current level to use with GAP 350mA LED fittings. Wire in series. Compatible with Triac and Phase cut dimmers.

PRODUCT FEATURES

- 25w constant current Triac dimmable LED driver
- Screw terminal connections
- For use with constant current LED luminaires
- For indoor use or within an enclosure
- PC housing
- Mounting tabs for securing to a flat surface
- Protections: Short Circuit / Over Load / Over Current
- Cooling by free air convection
- Dimming function: Triac dimmable; Phase Cut dimmable
- Suitable for interior architectural, retail and commercial applications.

PRODUCT DATA

Model	TDIM-25W-350								
Rated Current	300mA	350mA	500mA	550mA	650mA	700mA	850mA	900mA	
DC Voltage	3-50v	3-50v	3-50v	3-45v	3-38v	3-35v	3-30v	3-38v	
Rated Power	15.0w	17.5w	25w	24.7w	24.7w	24.5w	25.5w	25.2w	
AC Current	0.29A	0.34A	0.48A	0.43A	0.48A	0.48A	0.50A	0.50A	
Working Temp.	Ta 50°C Tc 90°C								
Protection	IP20								
Dimensions	L 155mm   W 54mm   D 20mm								
Current Tolerance	+/- 5%								
Voltage Range	180-240VAC 50-60Hz								
Full Load Efficiency	80% @ 350mA								
Over Load	≤120%								
Weight	21g								
Approvals	CE   SELV   RoHS								

COMPATIBILITY CHART

CODE	MAX LOAD	CODE	MAX LOAD
LED03	2-5	ML103	2-15
GL102/H/SQ	2-15	ML304	1-5
GL106/H/Q	2-15	ML0021	2-15
GL109/Q/QT	2-15	ML0022	1-7
GL0140	1-5		
GL121/122/123	2-15		
GL0151/2/4	1-5		
PL1021	2-15		
PL1023	1-5		
PL1026	1-2		
GLM12	1		

INSTALLATION

Please follow installation guide