

# TP(A) FIRE RATED LOW GLARE LED PANEL 600 X 600mm

36W

Fits in suspended ceiling grid. Direct replacement for  
fluorescent luminaires. Installs in minutes!



## FEATURES:

- Bright Source Premium LED backlit panel
- TP(a) rated
- UGR<19 Low Glare
- 3 colours available
- 5 year warranty
- 36W - 10% lower power consumption than standard panels
- Emergency, dimmable and sensor options available

## APPLICATIONS



EDUCATION



COMMERCIAL  
KITCHENS



OFFICES



RETAIL

BRIGTH SOURCE

**36W**

# TP(A) FIRE RATED LOW GLARE LED PANEL 600 X 600mm

Fits in suspended ceiling grid. Direct replacement for fluorescent luminaires. Installs in minutes!

Part No.	223757	223764	223771
<b>DESCRIPTION</b>	LED Panel 36W White Frame 3000K	LED Panel 36W White Frame 4000K	LED Panel 36W White Frame 6000K
<b>DIMENSIONS</b>	595 x 595 x 24mm		
<b>POWER CONSUMPTION</b>	36kWh/1000hrs		
<b>POWER FACTOR</b>	0.90		
<b>COLOUR TEMPERATURE</b>	3000K (Warm White)	4000K (Cool White)	6000K (Daylight White)
<b>COLOUR RENDITION (CRI)</b>	Ra>80		
<b>LUMENS</b>	3600lm		
<b>IP RATING</b>	IP20		
<b>BEAM ANGLE</b>	90°		
<b>SWITCHING CYCLES</b>	50,000		
<b>LIFETIME</b>	50,000h		
<b>CONSTRUCTION</b>	Polycarbonate, Aluminium and Steel		
<b>WORKING TEMPERATURES</b>	-20°C to +40°C		
<b>ENERGY CONSUMPTION</b>	F		
<b>DRIVER</b>	AGT		
<b>LOW GLARE</b>	UGR<19		
<b>CERTIFICATION</b>	UKCA,CE, RoHS		
<b>WARRANTY</b>	1 year (+ 4 years extended warranty with online registration)		
<b>SDCM</b>	6		
<b>L Value</b>	80		
<b>B Value</b>	10		
<b>Driver</b>	Tridonic		
<b>LED Chip Brand</b>	SANAN		
<b>IK Rating</b>	IK02		



# BRIGTH SOURCE



Formerly rated A+  
(same quality,  
new energy rating  
label regulations)

