TECHNICAL DATA

PROFILE & COVING

PRODUCT CODE

PROFILE7



WARRANTY

3 years guarantee

@GAPLightingLtd

GAP Lighting Ltd

/GAPLightingLtd

GAP Lighting Ltd



y



Surface mount aluminium channel for various LED striplights. Includes PC diffuser for anti-glare light output.









Plastic end caps

Plastic clips

PRODUCT FEATURES

Anodised Aluminium profile for mounting flexible LED striplight up to 12mm width

Create a solid fixture / continuous linear LED lighting system

Available in 1 and 2 metre lengths (silver finish) and 2 metre lengths (white finish)

Surface mount

Suitable for diverse interior applications

Not watertight

PRODUCT DATA

Model PROFILE7 PROFILE7-2 PROFILE7-2W Material Aluminium Polycarbonate Protection IP20 Colour Silver White channel Diffuser Anti-glare opaque Length 1 or 2 metres Application Surface mount Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm Approvals CE ROHS		
Protection IP20 Colour Silver White channel Diffuser Anti-glare opaque Length 1 or 2 metres Application Surface mount Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Model	PROFILE7 PROFILE7-2 PROFILE7-2W
Colour Silver White channel Diffuser Anti-glare opaque Length 1 or 2 metres Application Surface mount Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Material	Aluminium Polycarbonate
Diffuser Anti-glare opaque Length 1 or 2 metres Application Surface mount Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Protection	IP20
Length 1 or 2 metres Application Surface mount Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Colour	Silver White channel
Application Surface mount Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Diffuser	Anti-glare opaque
Installation Includes fixing clips and end caps Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Length	1 or 2 metres
Dimensions W 17.3mm D 7mm Internal Width 12.5mm	Application	Surface mount
	Installation	Includes fixing clips and end caps
Approvals CE ROHS	Dimensions	W 17.3mm D 7mm Internal Width 12.5mm
	Approvals	CE ROHS

Line Drawing

COMPATIBILITY

iFLEX / FLEX CCT / FLEX RGBW / FLEX-DMX / FLEX 20 / POWER FLEX / FLEX-LINE / FLEXI / FLEX 65

