

**7** 7 Years  
Product Warranty  
UK Only

**2** 2 Years  
On-Site Warranty  
Main-land UK Only




# Avon 4

08075 AVO45FT60-W40

## Avon 4 non-corrosive batten 5ft twin 34/44/52/60W 4000K

- T8 non-corrosive LED replacement
- Optional emergency module
- IP65 and vandal resistant
- Optional built-in ON/OFF microwave sensor
- Opal diffuser
- 20mm conduit entry



### Overview

The Kosnic Avon 4 LED non-corrosive battens utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications including warehouses, factories and garages. The product range has optional microwave sensor and emergency options.



**IP65**



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

### Technical Summary

Product Code	AVO45FT60-W40
Input Voltage Supply	220-240Vac 50/60Hz
Settable Wattages	34W, 44W, 52W, 60W
Power Factor	0.90
Default CCT	4,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	7,750 lm
Maximum Efficiency	139 lm/W
Maintained Luminous Flux	350 lm
L80B10 Lifetime (h) @Ta 25 °C	139,000 h
Nominal Lifetime (h)	50,000 h
Weight	2.15Kg
Dimensions (L x W x D) (mm)	1500x116x80



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)

**7** Years  
Product Warranty  
UK Only

**2** Years  
On-Site Warranty  
Main-land UK Only

# Avon 4



08075 AVO45FT60-W40

## Optional Gear

Product Code	Description	Type
BEM203	3W standard UEM for linear LED luminaire	Emergency Module
BEM203/ST	3W self-test UEM for linear LED luminaire	Self-test Emergency Module
BEM203/DA	Batten UEM DALI-2, 3W emergency module for Kosnic LED batten luminaires	Emergency Module
BEM303	Batten UEM 3W emergency module for batters	Emergency Module
BEM303/ST	Batten UEM 3W Self test emergency module for batters	Self-test Emergency Module
BEM303/DA	Batten UEM 3W DALI switchable for batters for batters	Emergency Module
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

## Accessories

Product Code	Description	Type
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS-BTN04/25	Batten Suspension Kits 2.5m length, 4 wires included	Suspension Kit

Power (W)	Length (ft)	Current (mA)	Lumen (lm)
34	5	164	4700
44	5	213	5800
52	5	251	6800
60	5	290	7750

## Overview

The Kosnic Avon 4 LED non-corrosive batters utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications including warehouses, factories and garages. The product range has optional microwave sensor and emergency options.




**IP65**



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External



Product Code	Length(mm)	Width(mm)	Depth(mm)
AVO44FS18	1200	91	78
AVO44FT36	1200	116	80
AVO45FS30	1500	91	78
AVO45FT60	1500	116	80

AVO44FS18  
AVO45FS30

AVO44FT36  
AVO45FT60



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com