

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only




Avon 4

08037 AVO46FT60-W40/S

Avon 4 sensor non-corrosive batten 6ft Twin 34/44/52/60W 4000K

- T8 non-corrosive LED replacement
- Optional emergency module
- IP65 and vandal resistant
- Optional built-in ON/OFF microwave sensor
- Opal diffuser
- 20mm conduit entry



Overview

The Kosnic Avon 4 LED non-corrosive battens utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications including warehouses, factories and garages. The product range has optional microwave sensor and emergency options.



IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Technical Summary

Product Code	AVO46FT60-W40/S
Input Voltage Supply	220-240Vac 50/60Hz
Settable Wattages	34W, 44W, 52W, 60W
Power Factor	0.90
Default CCT	4,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<1%
Lumens Output Maximum	7,750 lm
Maximum Efficiency	138 lm/W
Maintained Luminous Flux	350 lm
L80B10 Lifetime (h) @Ta 25 °C	139,000 h
Nominal Lifetime (h)	50,000 h
Weight	3.05Kg
Dimensions (L x W x D) (mm)	1836x120x76



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Avon 4



08037 AVO46FT60-W40/S

Optional Gear

Product Code	Description	Type
BEM203	3W standard UEM for linear LED luminaire	Emergency Module
BEM203/ST	3W self-test UEM for linear LED luminaire	Self-test Emergency Module
BEM203/DA	Batten UEM DALI-2, 3W emergency module for Kosnic LED batten luminaires	Emergency Module
BEM303	Batten UEM 3W emergency module for batters	Emergency Module
BEM303/ST	Batten UEM 3W Self test emergency module for batters	Self-test Emergency Module
BEM303/DA	Batten UEM 3W DALI switchable for batters for batters	Emergency Module
PIR-SID	P30 Exterior PIR Sensor Side-Mount with RMT-UNI control	PIR Sensor

Accessories

Product Code	Description	Type
SUS-BTN04	Suspension for Niva Kasai Kennet Milo Congo Trent Avon Indus, 4 wires included, max. 1m drop	Suspension Kit
SUS-BTN04/25	Batten Suspension Kits 2.5m length, 4 wires included	Suspension Kit

Power (W)	Length (ft)	Current (mA)	Lumen (lm)
34	6	164	4700
44	6	213	5800
52	6	251	6800
60	6	290	7750

Overview

The Kosnic Avon 4 LED non-corrosive batters utilise high performance LEDs to offer outstanding lumen efficiency and are suitable for a wide range of commercial applications including warehouses, factories and garages. The product range has optional microwave sensor and emergency options.





IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK08
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External



AVO46FS53 **AVO46FT60**

Product Code	Length(mm)	Width(mm)	Depth(mm)
AVO46FS53	1836	80	76
AVO46FT60	1836	120	76



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com