

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only



Napa Pro

08076 NAPP4IN12-SLV


Napa Pro 4 inch Commercial Downlight CCT switch 6W-12W Silver

- Switchable CCT (3000k/4000k/5700k)
- Long life of 50,000h
- High lumen output
- Low glare UGR <19
- Flicker free
- Integrated Dimmable driver
- Compatible with Kosnic's mains emergency module

Overview

Napa Pro LED Commercial

Downlight with a range of power settings and switchable colour temperature.



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP54
Nominal Lifetime (h)	50,000 h
Protection Rating	Class II
Installation Area	Internal

Technical Summary

Product Code	NAPP4IN12-SLV
Input Voltage Supply	220-240Vac 50/60Hz
Settable Wattages	6W, 8W, 10W, 12W
Driver Code/Part number	DR12C15-30
Driver Maximum Power (W)	12
Driver Output Current (mA)	150/200/250/300
Driver Power Factor	>0.9
Settable Colour Temperatures	3000k, 4000k, 5700k
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<1%
Maximum Efficiency	130 lm/W
Maintained Luminous Flux	320 lm
L80B10 Lifetime (h) @Ta 25 °C	78,000 h
Nominal Lifetime (h)	50,000 h
Weight	0.32Kg
Dimensions (L x W x D) (mm)	55xØ145
Cut-Out (mm)	Ø125



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

7 Years
Product Warranty
UK Only

2 Years
On-Site Warranty
Main-land UK Only

Napa Pro



08076 NAPP4IN12-SLV

Optional Gear

Product Code	Description	Type
UEM03	3W Universal Emergency Module	Emergency Module
UEM03/ST	3W Universal Emergency Module, Self Test	Self-test Emergency Module
UEM04	4W Universal Emergency Module Pro	Emergency Module
UEM04/ST	4W Universal Emergency Module Pro Self Test	Self-test Emergency Module
EMPAD01/ST	Neka self test 1W universal emergency pad for downlight	Self-test Emergency Module
DRC30/DA	Dimmable Driver: 30W DALI, 1-10V, Primary PUSH Driver	Dimmable Driver
EMPAD01	Neka, 1W universal emergency pad for downlight	Emergency Module

Accessories

Product Code	Description	Type
NAPP4IN-SUR	Napa Pro 4 inch surface mount frame	Mount Frame



Overview

Napa Pro LED Commercial Downlight with a range of power settings and switchable colour temperature.

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP54
Nominal Lifetime (h)	50,000 h
Protection Rating	Class II
Installation Area	Internal

Variables Settings

Rated Power (W)	Current (mA)	CCT (k)	Luminous Flux (lm)	Power Factor
6	29	3000 Warm White	720	0.9
6	29	4000 Cool White	780	0.9
6	29	5700 Day Light	780	0.9
8	39	3000 Warm White	960	0.9
8	39	4000 Cool White	1040	0.9
8	39	5700 Day Light	1040	0.9
10	46	3000 Warm White	1200	0.94
10	46	4000 Cool White	1300	0.94
10	46	5700 Day Light	1300	0.94
12	55	3000 Warm White	1440	0.95
12	55	4000 Cool White	1560	0.95
12	55	5700 Day Light	1560	0.95

Light Source only

Useful Luminous Flux (lm) at 55W	CCT (k)	Chromaticity co-ordinates (x)	Chromaticity co-ordinates (y)	R9 CRI	Peak Luminous Intensity
1340	3000	0.444	0.408	0	1440
1430	4000	0.375	0.370	15	1530
1430	5700	0.331	0.345	5	1530



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com





7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Napa Pro



08076 NAPP4IN12-SLV



Overview

Napa Pro LED Commercial
Downlight with a range of power
settings and switchable colour
temperature.



IP54



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK04
IP Rating	IP54
Nominal Lifetime (h)	50,000 h
Protection Rating	Class II
Installation Area	Internal



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com