

# Cirrus II

07817 CIR2200-W50

## Cirrus II Ultra slim highbay 100/150/200W 5000K

- Ultra slim body
- Wattage switching model of 80W/100W/120W/150W and model of 100W/150W/200W
- Optional plug-in emergency
- Diecast aluminium
- IP65 & vandal resistant (IK10)
- Flicker free

### Overview

The Cirrus II High Bay luminaire provides energy savings and high performance, replacing conventional lighting in general industrial areas, manufacturing, warehousing, leisure facilities and retail environments. With versatile switchable wattage and CCT.



**IP65**



### General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Materials	Housing Diecast aluminium
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal

### Technical Summary

Product Code	CIR2200-W50
Input Voltage Supply	220-240Vac 50/60Hz
Settable Wattages	100W, 150W, 200W
Power Factor	0.95
Default CCT	5,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	<30%
Lumens Output Maximum	31,000 lm
Maximum Efficiency	175 lm/W
Maintained Luminous Flux	900 lm
L80B10 Lifetime (h) @Ta 25 °C	54,000 h
Nominal Lifetime (h)	50,000 h
Weight	2.28Kg
Dimensions (L x W x D) (mm)	82xØ320



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

# Cirrus II

07817 CIR2200-W50

## Optional Gear

Product Code	Description	Type
EMHB10	10W standard Universal Emergency Module for LED high bay	Emergency Module
EMHB10/ST	10W self-test Universal Emergency Module for LED high bay	Self-test Emergency Module
MWS-ZGA	Zhaga microwave motion sensor, 1-10V dim output	Microwave Sensor
PIR-ZGA	PIR sensor with Zhaga connector with ON/OFF 0-10V Dimming	PIR Sensor
EMHB08	8W standard Universal Emergency Module for LED high bay	Emergency Module
EMHB08/ST	8W self-test Universal Emergency Module for LED high bay	Self-test Emergency Module

## Overview


The Cirrus II High Bay luminaire provides energy savings and high performance, replacing conventional lighting in general industrial areas, manufacturing, warehousing, leisure facilities and retail environments. With versatile switchable wattage and CCT.

Rated Power (W)	Current (mA)	CCT (K)	Total Lumen (lm)
100	457	5000	17500
150	686	5000	23400
200	915	5000	31000



## General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Materials	Housing Diecast aluminium
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com