

# Arden II



08253 ARDF10T-BLK

# Arden II Aluminium bollard flat head 120x1020mm 10W CCT

- Die-cast aluminium body with polycarbonate diffuser
- Options of various heights
- Internal stainless steel reflector
- Black or dark grey textured powder coat finishing
- Sensor options available
- Root mount included



Technical Summary				
Product Code	ARDF10T-BLK			
Input Voltage Supply	220-240Vac 50/60Hz			
Default Power	10 W			
Power Factor	0.9			
Settable Colour Temperatures	3000k, 4000k, 5000k			
SDCM of CCT	<6			
CRI	82			
Dimmable	N			
Flicker	<5%			
Lumens Output Maximum	780 lm			
Maximum Efficiency	78 lm/W			
L80B10 Lifetime (h) @Ta 25 °C	54,000 h			
Nominal Lifetime (h)	50,000 h			
Weight	2.85Kg			
Dimensions (L x W x D) (mm)	990xØ120			

# Overview

The Arden II LED Bollards offer affordable products with high lumen efficiency and a long life. The weather resistant bollards are perfectly suited for commercial and domestic outdoor illumination and is available in black or grey with a choice of wattage and height.



# General Information

Ambient	-20°C to 50°C		
Temperature			
Range (°C)			
IP Rating	IP65		
Nominal	50,000 h		
Lifetime (h)			
Protection	Class I		
Rating			
Installation	External		
Area			



KosnicUK

KosnicLightingUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com





#### 08253 ARDF10T-BLK

#### Overview

The Arden II LED Bollards offer affordable products with high lumen efficiency and a long life. The weather resistant bollards are perfectly suited for commercial and domestic outdoor illumination and is available in black or grey with a choice of wattage and height.

5 Years Product Warranty

UK Only



### General Information

Ambient	-20°C to 50°C
Temperature	
Range (°C)	
IP Rating	IP65
Nominal	50,000 h
Lifetime (h)	
Protection	Class I
Rating	
Installation	External
Area	

\_









KosnicLightingUK

Tel: 01635 523 713

Kosnic.com

Email: sales@kosnic.com

	ССТ	Luminous Flux (lm)	Light Source Luminous Flux (lm)	5	Chromaticity Co- Ordinates (y )
	3000k	750	1390	0.436	0.405
ł	4000k	780	1420	0.390	0.380
	5000k	750	1390	0.350	0.362

