

### Overview

The Arden II LED Bollards offer affordable products with high lumen efficiency and a long life. The weather resistant bollards are perfectly suited for commercial and domestic outdoor illumination and is available in black or grey with a choice of wattage and height.







#### General Information

Ambient	-20°C to 50°C		
Temperature			
Range (°C)			
IP Rating	IP65		
Nominal	50,000 h		
Lifetime (h)			
Protection	Class I		
Rating			
Installation	External		
Area			





Kosnic Lighting





KosnicLightingUK
Tel: 01635 523 713

KosnicUK

Email: sales@kosnic.com

Kosnic.com

# Arden II



08254 ARDF10T-GRY

### Arden II Aluminium bollard flat head 120x1020mm 10W CCT

- Die-cast aluminium body with polycarbonate diffuser
- Options of various heights
- Internal stainless steel reflector
- Black or dark grey textured powder coat finishing
- Sensor options available
- Root mount included



Technical Summary				
Product Code	ARDF10T-GRY			
Input Voltage Supply	220-240Vac 50/60Hz			
Default Power	10 W			
Power Factor	0.9			
Settable Colour Temperatures	3000k, 4000k, 5000k			
SDCM of CCT	<6			
CRI	82			
Dimmable	N			
Flicker	<5%			
Lumens Output Maximum	780 lm			
Maximum Efficiency	78 lm/W			
L80B10 Lifetime (h) @Ta 25 °C	54,000 h			
Nominal Lifetime (h) 50,000 h				
ght 2.85Kg				
Dimensions (L x W x D) (mm)	990x∅120			



## Overview

The Arden II LED Bollards offer affordable products with high lumen efficiency and a long life. The weather resistant bollards are perfectly suited for commercial and domestic outdoor illumination and is available in black or grey with a choice of wattage and height.







### General Information

Ambient	-20°C to 50°C		
Temperature			
Range (°C)			
IP Rating	IP65		
Nominal	50,000 h		
Lifetime (h)			
Protection	Class I		
Rating			
Installation	External		
Area			





Kosnic Lighting





 ${\it Kosnic Lighting UK}$ 

KosnicUk

Tel: 01635 523 713
Email: sales@kosnic.com

Kosnic.com

# Arden II



### 08254 ARDF10T-GRY

ССТ	Luminous Flux (lm)	Light Source Luminous Flux (lm)	ĺ	Chromaticity Co- Ordinates (y )
3000k	750	1390	0.436	0.405
4000k	780	1420	0.390	0.380
5000k	750	1390	0.350	0.362

