

Forbury

06556 FOR15T-BLK

Forbury Aluminium die-cast bollard integrated LED 15W 4000K

- Die-cast aluminium body with polycarbonate diffuser
- Black or dark grey textured powder coat finishing
- Options of 2 different heights



Overview

The Forbury offers an affordable product with high lumen efficiency and a long life. The bollards are made from die-cast aluminium with a polycarbonate diffuser. They are available in black or grey with a choice of two heights.



IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	External

Technical Summary

Product Code	FOR15T-BLK
Input Voltage Supply	110-240Vac 50/60Hz
Default Power	15 W
Power Factor	0.92
Default CCT	4,000 K
CRI	≥82
Dimmable	N
Lumens Output Maximum	530 lm
Maximum Efficiency	35 lm/W
L80B10 Lifetime (h) @Ta 25 °C	54,000 h
Nominal Lifetime (h)	50,000 h
Weight	3.45Kg
Dimensions (L x W x D) (mm)	800xØ120



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

06556 FOR15T-BLK

Overview

The Forbury offers an affordable product with high lumen efficiency and a long life. The bollards are made from die-cast aluminium with a polycarbonate diffuser. They are available in black or grey with a choice of two heights.



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	External



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com