

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only




Pollux

07918 PLX08-SCT

Pollux 8W mains dimmable slim LED wall light CCT switchable

- CCT switchable 3000K/4000k/5000K
- Flicker free
- Up and down luminous function



Overview

The Pollux slim profile LED wall light offers a low maintenance solution to lighting for all areas, with switchable CCT to meet your different ambient needs.



IP20



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK03
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Technical Summary

Product Code	PLX08-SCT
Input Voltage Supply	220-240Vac 50/60Hz
Default Power	8 W
Power Factor	0.95
Default CCT	4,000 K
Settable Colour Temperatures	3000k, 4000k, 5000k
SDCM of CCT	<6
CRI	81
Dimmable	Y
Flicker	<1%
Lumens Output Maximum	790 lm
Maximum Efficiency	99 lm/W
L80B10 Lifetime (h) @Ta 25 °C	54,000 h
Nominal Lifetime (h)	50,000 h
Weight	0.53Kg
Dimensions (L x W x D) (mm)	180x90x38.5



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

7 7 Years
Product Warranty
UK Only

2 2 Years
On-Site Warranty
Main-land UK Only

Pollux




07918 PLX08-SCT

Power (W)	CCT (K)	Lumen (lm)
8	3000	760
8	4000	790
8	5000	790

Overview

The Pollux slim profile LED wall light offers a low maintenance solution to lighting for all areas, with switchable CCT to meet your different ambient needs.



PLX08-SCT

General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK03
IP Rating	IP20
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com