

Tarkine solar

06783 TARS-W-BLK

Tarkine Solar Aluminium diecast wall light 4000K Black

- Integrated high output polycrystalline silicon solar panel
- Multiple operation mode with different light level setting
- Built-in PIR and daylight sensor
- Die-cast aluminium body with polycarbonate diffuser
- Wall mount options available
- Built in solar panel
- Options of various heights
- Black or dark grey textured powder coat finishing



Overview

The Tarkine Solar offers an affordable product with high lumen efficiency and a long life. The bollards are made from die-cast aluminium with a polycarbonate diffuser and features an integrated polycrystalline solar panel. They are available in black or grey with a choice of heights.



IP65



General Information

Ambient Temperature Range (°C)	-10°C to 40°C
IP Rating	IP65
Nominal Lifetime (h)	25,000 h
Protection Rating	Class III
Installation Area	External

Technical Summary

Product Code	TARS-W-BLK
Default Power	4.5 W
Default CCT	4,000 K
CRI	80
Dimmable	N
Lumens Output Maximum	250 lm
Maximum Efficiency	56 lm/W
Nominal Lifetime (h)	25,000 h
Weight	1.53Kg
Dimensions (L x W x D) (mm)	220xØ220



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713


Email: sales@kosnic.com

Kosnic.com

06783 TARS-W-BLK

Overview

The Tarkine Solar offers an affordable product with high lumen efficiency and a long life. The bollards are made from die-cast aluminium with a polycarbonate diffuser and features an integrated polycrystalline solar panel. They are available in black or grey with a choice of heights.



General Information

Ambient Temperature Range (°C)	-10°C to 40°C
IP Rating	IP65
Nominal Lifetime (h)	25,000 h
Protection Rating	Class III
Installation Area	External



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com