

# Tarkine Solar

06574 TARS-T-GRY

## Tarkine Solar Aluminium diecast Tall bollard 4000K Grey

- Integrated high output polycrystalline silicon solar panel
- Multiple operation mode with different light level setting
- Built-in PIR and daylight sensor
- Die-cast aluminium body with polycarbonate diffuser
- Wall mount options available
- Built in solar panel
- Options of various heights
- Black or dark grey textured powder coat finishing



### Overview

The Tarkine Solar offers an affordable product with high lumen efficiency and a long life. The bollards are made from die-cast aluminium with a polycarbonate diffuser and features an integrated polycrystalline solar panel. They are available in black or grey with a choice of heights.



**IP65**



### General Information

|                                |               |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -10°C to 40°C |
| IP Rating                      | IP65          |
| Nominal Lifetime (h)           | 25,000 h      |
| Protection Rating              | Class III     |
| Installation Area              | External      |

### Technical Summary

|                             |            |
|-----------------------------|------------|
| Product Code                | TARS-T-GRY |
| Default Power               | 4.5 W      |
| Default CCT                 | 4,000 K    |
| CRI                         | 80         |
| Dimmable                    | N          |
| Lumens Output Maximum       | 250 lm     |
| Maximum Efficiency          | 56 lm/W    |
| Nominal Lifetime (h)        | 25,000 h   |
| Weight                      | 2.5Kg      |
| Dimensions (L x W x D) (mm) | 810xØ220   |



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713


Email: sales@kosnic.com

Kosnic.com

06574 TARS-T-GRY

## Overview

The Tarkine Solar offers an affordable product with high lumen efficiency and a long life. The bollards are made from die-cast aluminium with a polycarbonate diffuser and features an integrated polycrystalline solar panel. They are available in black or grey with a choice of heights.



## General Information

|                                |               |
|--------------------------------|---------------|
| Ambient Temperature Range (°C) | -10°C to 40°C |
| IP Rating                      | IP65          |
| Nominal Lifetime (h)           | 25,000 h      |
| Protection Rating              | Class III     |
| Installation Area              | External      |



Kosnic Lighting



KosnicUK



KosnicLightingUK



KosnicUK

Tel: 01635 523 713

Email: [sales@kosnic.com](mailto:sales@kosnic.com)

[Kosnic.com](http://Kosnic.com)